

PowerWash™ XT Features:

- USDA-approved, white epoxy RUST-OLEUM® paint
 - 303 Stainless steel shaft with spring loaded contact seals in each endshield
 - Stainless steel fan guard (56-145T frames) or epoxy coated fan guard (182T-215T frames)
 - Cast conduit box with threaded openings, stainless steel cover
 - Internal corrosion resistant coatings on frame, base, endshields, rotor and stator
 - Double sealed ball bearings
 - Plugged drain holes in each endshield for all angle mounting
 - 1.15 Service factor OR Variable torque (6-60Hz) 1.0 Service Factor on VFD
 - UL Recognized and CSA Certified, CE Mark
 - Marathon Electric provides 1 Year warranty
- + MT Discount Code**



| HP | RPM | Volts | Frame | Enc | Notes | Cat No. | List Price | Weight (lbs) | Lead-time (Days) | CT Range | Nominal Efficiency | F.L. Amps | "C" |
|-----|------|-------------|-------|------|--------------------|---------|------------|--------------|------------------|----------|--------------------|----------------|-------|
| 1/3 | 1800 | 208-230/460 | 56C | TENV | | CTN565 | \$626 | 23 | 5 | 6:1 CT | 72 | 1.3-1.3/65 | 10.08 |
| 1/2 | 3600 | 208-230/460 | 56C | TENV | | CTN566 | \$590 | 30 | 5 | 6:1 CT | 76 | 1.5-1.5/75 | 10.58 |
| 1/2 | 1800 | 208-230/460 | 56C | TENV | | CTN567 | \$660 | 26 | 5 | 6:1 CT | 78.5 | 1.8-1.8/9 | 10.06 |
| 3/4 | 3600 | 208-230/460 | 56C | TENV | | CTN569 | \$647 | 24 | 5 | 6:1 CT | 75.5 | 2.4-2.4/1.2 | 10.08 |
| 3/4 | 1800 | 208-230/460 | 56C | TENV | | CTN599 | \$764 | 33 | 5 | 6:1 CT | 80 | 2.5-2.5/1.25 | 10.56 |
| 1 | 3600 | 208-230/460 | 56C | TENV | | CTN601 | \$757 | 35 | 5 | 6:1 CT | 78.5 | 2.6-2.6/1.3 | 11.56 |
| 1 | 1800 | 208-230/460 | 56C | TENV | | CTN602 | \$797 | 36 | 5 | 6:1 CT | 80 | 3.2-3.2/1.6 | 11.58 |
| 1 | 1200 | 208-230/460 | 56HC | TEFC | Combo Base | CTN604 | \$961 | 26 | 5 | 3:1 CT | 78.5 | 3.0-3.0/1.5 | 13.06 |
| 1.5 | 3600 | 208-230/460 | 56C | TENV | | CTN605 | \$836 | 44 | 5 | 6:1 CT | 80 | 3.8-3.8/1.9 | 12.56 |
| 1.5 | 1800 | 208-230/460 | 56C | TENV | | CTN606 | \$832 | 34 | 5 | 6:1 CT | 84 | 4.2-4.2/2.1 | 13.06 |
| 1.5 | 1800 | 208-230/460 | 145TC | TENV | | CTN607 | \$832 | 48 | 5 | 6:1 CT | 84 | 4.2-4.2/2.1 | 13.12 |
| 1.5 | 1200 | 208-230/460 | 56HC | TEFC | Combo Base | CTN608 | \$1,015 | 31 | 5 | 3:1 CT | 77 | 5.7-5.7/2.85 | 14.18 |
| 2 | 3600 | 208-230/460 | 56HC | TENV | Combo Base, 1.0 SF | CTN609 | \$928 | 48 | 5 | 6:1 CT | 82.5 | 5.0-5.0/2.5 | 13.06 |
| 2 | 3600 | 208-230/460 | 145TC | TENV | | CTN610 | \$1,029 | 47 | 5 | 6:1 CT | 82.5 | 5.0-5.0/2.5 | 13.25 |
| 2 | 1800 | 208-230/460 | 56C | TEFC | | CTN611 | \$954 | 39 | 5 | 3:1 CT | 81.5 | 6.2-6.2/3.1 | 12.69 |
| 2 | 1800 | 208-230/460 | 145TC | TEFC | | CTN612 | \$1,029 | 46 | 5 | 3:1 CT | 84 | 6.0-6.0/3.0 | 13.12 |
| 3 | 3600 | 208-230/460 | 145TC | TEFC | | CTN613 | \$1,214 | 45 | 5 | 3:1 CT | 85.5 | 7.4-7.4/3.7 | 12.62 |
| 3 | 1800 | 208-230/460 | 182TC | TEFC | | CTN1614 | \$1,353 | 65 | 5 | 10:1 CT | 87.5 | 8.8-8.4/4.2 | 14.47 |
| 5 | 3600 | 208-230/460 | 184TC | TEFC | | CTN1615 | \$1,694 | 77 | 5 | 3:1 CT | 87.5 | 13.4-12.2/6.1 | 14.47 |
| 5 | 1800 | 208-230/460 | 184TC | TEFC | | CTN616 | \$1,529 | 90 | 5 | 3:1 CT | 87.5 | 13.8-13.0/6.5 | 14.97 |
| 7.5 | 3600 | 208-230/460 | 213TC | TEFC | | CTN617 | \$2,103 | 120 | 5 | 3:1 CT | 88.5 | 17.6-16.8/8.4 | 17.47 |
| 7.5 | 1800 | 208-230/460 | 213TC | TEFC | | CTN618 | \$1,939 | 145 | 5 | 3:1 CT | 89.5 | 20.4-20.4/10.2 | 17.71 |
| 10 | 1800 | 208-230/460 | 215TC | TEFC | | CTN619 | \$2,204 | 145 | 5 | 3:1 CT | 89.5 | 26.0-26.0/13.0 | 18.71 |

Combo Base includes 12 mounting holes for 56H, 143T, and 145T mounting locations